
# SKYLINE LANDFILL

# APPENDIX G4 LANDFILL GAS COLLECTION SYSTEM EXISTING CONDITIONS

30 TAC §330.371



# SKYLINE LANDFILL CITY OF FERRIS DALLAS AND ELLIS COUNTIES, TEXAS TCEQ PERMIT NO. MSW 42D

# PERMIT AMENDMENT APPLICATION

## PART III – FACILITY INVESTIGATION AND DESIGN APPENDIX G5 LANDFILL GAS CONTROL SYSTEM DESIGN

Prepared for

Waste Management of Texas, Inc.

April 2012

Revised August 2012



Prepared by

Weaver Boos Consultants, LLC-Southwest
TBPE Registration No. F-3727
6420 Southwest Blvd., Suite 206
Fort Worth, Texas 76109

817-735-9770

#### **CONTENTS**

1	LFG	SYSTEM	G5_1
	1.1	Existing LFG Collection and Control System.	C5 1
	1.2	Future GCCS Expansions	G5-1

#### **APPENDIX G5-A**

Landfill Gas Collection and Control System Plan

#### **APPENDIX G5-B**

Landfill Gas Generation Model



# 1.1 Existing LFG Collection and Control System

Currently, the site has an active LFG collection and control system (GCCS), as shown in Appendix G5-A on Drawing G5-A-1. The site has a design capacity greater than 2.5 million megagrams and 2.5 million cubic meters, and has a nonmethane organic compound (NMOC) emission rate greater than 50 megagrams per year. This makes the facility subject to the requirements under 40 CFR Part 60, Subpart WWW, New Source Performance Standards for Municipal Solid Waste Landfills (NSPS). As a result, the existing GCCS will be required to begin operating in accordance with NSPS requirements on April 29, 2013.

The existing GCCS consists of vertical LFG extraction wells, a piping network, a condensate management system, a blower/flare facility, and a Waste Management owned and operated landfill gas-to-energy (LFGTE) facility. The existing blowers provide vacuum to the extraction wells through the LFG collection piping network. The extracted LFG is routed from the collection points to the LFGTE facility, which uses extracted LFG from the landfill as fuel to generate electricity. Any remaining extracted LFG not sent to the LFGTE facility is diverted to an on-site flare where the gas is combusted.

As additional waste is placed, the existing LFG extraction wells will be extended and/or redrilled.

### 1.2 Future GCCS Expansions

As the site develops, additional extraction wells will be installed as needed to reduce the buildup of internal gas pressures caused by the increased generation of LFG and to comply with the requirements under 40 CFR Part 60, Subpart WWW. The locations of the anticipated future vertical extraction wells are shown on Drawing G5-A-1.

Two Three vertical extraction well alternatives are proposed for different final cover areas, as shown on Drawings G5-A-2 and G5-A-3. In areas with Subtitle D final cover and alternate final cover, extraction wells will be constructed as shown on Details LFG-1 and LFG-2, respectively. If additional wells or redrills are needed in areas with pre-Subtitle D final cover, the vertical extraction wells will be constructed as shown on Detail LFG-23.

Each LFG extraction well will consist of a perforated pipe within a gravel backfill. The LFG extraction wells will be installed in phases as needed as the landfill develops. The

exact number and location of wells, horizontal collectors, piping, and future LFG facilities will be determined based on field conditions at the time of installation.

Using the EPA Landfill Gas Emissions Model, it is estimated that the site will generate a maximum of approximately 13,315 standard cubic feet per minute (scfm) of LFG in 2044 (Appendix G5-B). As such, blowers and piping network will be installed as needed to provide the vacuum and capacity to handle the predicted maximum flow rate of LFG. In addition, each extraction well will be equipped with a control valve and monitoring port, as shown on Drawing G5-A-2. These control valves and monitoring ports, used in conjunction with controls on the blower, will allow the site to regulate vacuum and LFG levels at each individual extraction well. This will allow the site to make adjustments in order to effectively collect LFG.

The operation and maintenance of the proposed LFG system will be performed consistent with industry guidelines and practices. Wellhead and system monitoring will be performed on a routine basis to monitor overall system performance. As needed, system adjustments will be made to optimize the extraction of LFG from the landfill to control LFG migration, odors, and greenhouse gases. In addition, the system will be routinely visually inspected for any evidence of needed repairs or other maintenance. General maintenance procedures will include the following:

- Each wellhead will be monitored and adjusted as needed to control LFG while reducing oxygen intrusion into the landfill.
- Condensate sumps will be checked for proper operation.
- Blowers and flares will be inspected for proper operation.


The system has been designed to include isolation valves and a looped piping network to allow the site to be adjusted, maintained, and quickly repaired.


# SKYLINE LANDFILL

# APPENDIX G5-A LANDFILL GAS COLLECTION AND CONTROL SYSTEM PLAN



Includes Drawings G5-A-1 and Through G5-A-23






TYPICAL LFG EXTRACTION WELL
IN SUBTITLE D FINAL COVER

NTS

S-1-2



TYPICAL LFG EXTRACTION WELL IN ALTERNATE FINAL COVER

9 2400 PL

J. HEATH PARKER

8/21/12


#### NOTES:

- 1. ALL SIZES AND DIMENSIONS ARE APPROXIMATE.
- 2. THE EXACT WELLHEAD CONFIGURATION DEPENDS ON MANUFACTURER.
- 3. THE ELEVATION OF THE EXISTING LINER SYSTEM WILL BE VERIFIED PRIOR TO CONSTRUCTION. THE VERIFICATION PROCESS WILL INCLUDE THE REVIEW OF EXISTING AS—BUILT LINER CERTIFICATION INFORMATION.
- 4. UPPER BENTONITE PLUG WILL COINCIDE WITH THE LOCATION OF THE COMPACTED SOIL.

DRAFT  X FOR PERMITTING PURPOSES ONLY  INSUED FOR CONSTRUCTION  CLIENT APPROVAL BY:			PREPARED FOR WASTE MANAGEMENT OF TEXAS, INC.			MAJOR PERMIT AMENDMENT TYPICAL EXTRACTION WELL DETAILS
	DATE: 04/2012 FILE: 0086-11-17 CAD: G5-A-2 WELL DETAILS.DWG	DRAWN BY: VRS DESIGN BY: SR REVIEWED BY: JHP			REVISIONS	SKYLINE RECYCLING & DISPOSAL FACILITY
ı			HO.	DATE	DESCRIPTION	DALLAS & ELLIS COUNTIES, TEXAS
			1	08/2012	TOEG 141 HOD COMMENT RESPONSE	DV D 00 11 1
					Weaver Boos Consultants	
Ì	PRESS OF DOCUMENTS THIS DOCUMENT, AND THE DESIGNS RESPONSED INSERT, AS AN INSTRUMENT OF PROFESSIONAL SOURCE, AS THE PROFESSION SOURCE OF THE PROFE				***************************************	TBPE REGISTRATION NO. F-3727
						CHECAGO, R. FORT WORTH, TX. CREAND RUPROS, M. HAPPENGLE, R. SOUTH BEND, N. TOTALETILLO OF A S.
						COLUMBRIS, OH EVANSAULE, IN SOUTH BEND, IN DRAWING G5-A-2 ORANGE, CO SINCERSIDE, MO CLEARWORT, FL.

0:\0086\11\EXPANSION LGMP (03-12)\nod\G5-A-2-WKL DKTAI

COPYRIGHT @ 2012 NEAVER BOOK CONSLETANTS, LLC. ALL RIGHTS RESERVED.



TYPICAL LFG EXTRACTION WELL (FG-3)
IN PRE-SUBTITLE D FINAL COVER (65-4-3)
NTS

#### NOTES:

- 1. ALL SIZES AND DIMENSIONS ARE APPROXIMATE.
- 2. THE EXACT WELLHEAD CONFIGURATION DEPENDS ON MANUFACTURER.
- 3. THE ELEVATION OF THE EXISTING LINER SYSTEM WILL BE VERIFIED PRIOR TO CONSTRUCTION. THE VERIFICATION PROCESS WILL INCLUDE THE REVIEW OF EXISTING AS-BUILT LINER CERTIFICATION INFORMATION.
- 4. UPPER BENTONITE PLUG WILL COINCIDE WITH THE LOCATION OF THE COMPACTED SOIL.

MAJOR PERMIT AMENDMENT TYPICAL EXTRACTION WELL DETAIL

SKYLINE RECYCLING & DISPOSAL FACILITY DALLAS & ELLIS COUNTIES, TEXAS

Weaver Boos Consultants
TBPE REGISTRATION NO. F-3727
CHICAGO, IL FORT WORTH, TX GRAND RAPES, MI
COLUMBUS, OH EXAMSMILE IN SOUTH BEND, IN

DRAWN BY: VRS DATE: 08/2012 FILE: 0086-11-17
REVIEWED BY: JHP CAD: WELL-DETAILDING DRAWING G5-A-